



# DS SERIES

## MEDIUM DUTY RAIL GATE

1,600 lb.– 3,000 lb. Capacities

**Level Ride Offers Better  
Load Stability Versus  
Tuckaway Design.**

Products shown may feature optional equipment.  
Content subject to change without notice.



### STANDARD DS SERIES ADVANTAGES INCLUDE:

- Applications - straight trucks, cube or cutaway vans, step vans, dual wheel service bodies and trailers
- Level ride lift - maximum load stability, with straight vertical platform movement
- Large folding platform stows at bed height for uninhibited rear door access and dock loading
- Simple and easy operation when opening and closing the platform (torsion bar assist)
- Easy cargo loading with standard 12" ramp
- Above floor lift feature with a maximum above floor travel of 11"
- UHMW - Slide pads on runners

### OTHER STANDARD FEATURES:

- Power unit installed, tested and enclosed in weather protected housing
- Platform folds in half on all standard models
- Anti-skid treadplate platform and ramp for better grip
- Built-in toe deflector
- Pressure compensated flow control valve controls platform descent regardless of load weight
- Weather sealed electric controls
- Charge line circuit protection
- Meets TMC specifications
- Powder coat finish on key liftgate components produces a high-quality finish that is exceptionally resistant to corrosion and abrasion

**Provides the convenience of a folding platform that stores at bed height.**



# DS SERIES

## MEDIUM DUTY RAIL GATE



### SPECIFICATIONS

Bed Ht: 38"- 57"

MODEL	CAPACITY	PLATFORM	RAMP
DS-16	1,600 lbs.	36" x 89"	12"
DS-20	2,000 lbs	36" x 89"	12"
DS-20	2,000 lbs	42" x 88"	12"
DS-30	3,000 lbs	42" x 88"	12"
<b>AP (Aluminum Platform)</b>			
DS/AP-16	1,600 lbs.	36" x 89"	12"
DS/AP-20	2,000 lbs	36" x 89"	12"
DS/AP-20	2,000 lbs	42" x 88"	12"
DS/AP-30	3,000 lbs	42" x 88"	12"

Note: Above floor models are available with a maximum above floor travel of 11"; All platforms break evenly

### OPTIONAL EQUIPMENT:

- Platform Material:
  - Aluminum
- Oversized Ramp in aluminum or steel:
  - Fixed
  - Hinged
  - with Cart Stop
- Deeper, narrower or wider platforms
- Above floor lift ( standard on all AF models ) lifts the platform with a maximum above floor travel of 11"
- Remote hand held toggle switch control with 15 ft. coil cord
- Hydraulic platform closing - decreases platform and rail width
  - Discuss with factory prior to ordering

# WALTCO

T: 800.211.3074  
F: 800.211.3075  
Email: sales@waltco.com  
Web: [www.waltcoliftgates.com](http://www.waltcoliftgates.com)

**Waltco Lift Corp.**  
**Corporate Office United States**  
285 Northeast Ave.  
Tallmadge, OH 44278  
P: 330.633.9191  
F: 330.633.1418

**Waltco Lift Corp.**  
**United States**  
620 S Hambledon Ave.  
City of Industry, CA 91744  
P: 626.964.0990  
F: 626.964.0149

**Waltco Lift Inc.**  
**Canada**  
90 North Queen St.  
Etobicoke, ON M8Z 2C5